



# The better battery

## PowerX

### The better modularity

5.0 up to 15.0 kWh per battery system  
Up to 2 battery systems, 30 kWh capacity

### The better security

LFP chemistry in unibody design  
Peace of mind installation

### The better installability

Tool-free click-and-connect system  
Pre-assembled plug & play cable for inverter connection

### The better flexibility

Upgradable capacity during lifetime  
Operating voltage from 350 up to 980V

## Technical data and types


Battery system (Genius box + battery modules)	FIM-BATT-5.0	FIM-BATT-10.0	FIM-BATT-15.0
<b>General specifications</b>			
Cell chemistry	Lithium-iron phosphate (LiFePO4)		
Battery module	PowerX - 5kWh		
Battery module energy	5 kWh		
Number of battery modules	1	2	3
Battery usable energy <sup>1)</sup>	5 kWh	10 kWh	15 kWh
Max. output power	2.5 kW	5 kW	5 kW
Peak output power	3.5 kW, 10 s	7 kW, 10 s	7 kW, 10 s
DC Nominal voltage (single-phase system)	450 V		
DC Operating voltage range (single-phase system)	350 ... 560 V		
DC Nominal voltage (three-phase system)	600 V		
DC Operating voltage range (three-phase system)	600 ... 980 V		
<b>Communication</b>			
Display	LED indicator, SOC status indicator		
Communication <sup>2)</sup>	RS485/CAN		
<b>Environmental</b>			
Environmental protection rating	IP66		
Operative ambient temperature <sup>3)</sup>	-20 °C to +55 °C (-4 °F to +131 °F)		
Max. operating altitude <sup>4)</sup>	4,000 m (13,123 ft.) (Derating above 2,000 m)		
Environment <sup>5)</sup>	Outdoor (Please refer to the user manual for installation condition)		
Relative humidity	5%-95%		
Cooling	Natural convection		
Noise emission	< 29 dB		
<b>General Specification</b>			
Dimensions (W x D x H)	670 mm x 150 mm x 600 mm	670 mm x 150 mm x 960 mm	670 mm x 150 mm x 1320 mm
Weight (Floor stand toolkit included)	63.8 kg (140.7lb)	113.8 kg (250.9lb)	163.8 kg (361.1lb)
Power module dimension (W x D x H)	670 mm x 150 mm x 240 mm		
Power module weight	12 kg		
Battery module dimensions (W x D x H)	670 mm x 150 mm x 360 mm		
Battery module weight <sup>6)</sup>	50 kg		
Installation	Floor stand (standard), Wall mounting (optional) <sup>7)</sup>		
Scalability	Max. 2 systems in parallel operation		
Compatible inverters	PowerUNO and PowerTRIO inverter families		
<b>Safety</b>			
Marking	CE, cTUVus		
Certificates	CEI 0-21, IEC 62109, IEC 62477, IEC/EN 61000, VDE AR-N-4105 AS NZS 4777, G98/99, RoHS		

- 1) Test conditions: 100% depth of discharge (DoD), 0.2C rate charge & discharge at 25°C, at the beginning of life. If no PV modules are installed or the system has not detected sunlight for at least 24 hours, the minimum end of discharge SOC is 15%
- 2) CAN is used only for parallel communication.
- 3) Refer to battery warranty letter for conditional application.
- 4) The output power may be affected by altitude. Please refer to the output derating curve for details.
- 5) Improper storage system installation may compromise product warranty and

- operation safety. Please follow the user manual during the installation, use, and maintenance of the storage system.
- 6) The weight of the battery modules varies with products, with a tolerance of ±3%.
  - 7) Dedicated installation kit required, to be purchased upon request.

#### Remarks:

- Features not specifically listed in the present data sheet are not included in the product



**12 kg**  
power module weight

**+40 %**  
time saving  
for commissioning

**5 kW**  
battery module power

  
module Tool-free  
click-and-connect

**Easy and safe**  
transportation and  
installation

**LiFePO4**  
Lithium iron phosphate


PowerX  
5.0 kWh



PowerX  
15 kWh



30 kWh system with 2 PowerX



## The better configurations



For more information please contact your local FIMER representative or visit:

fimer.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. FIMER does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of FIMER. Copyright© 2024 FIMER. All rights reserved.

